

Engine	Perkins1104D-44T
Gross Power	74.5 kw (101 hp) @ 2,200 rpm
Net Power	72 kW (98 hp) @ 2,200 rpm
Maximum Speed	41 km/h
Standard Loader Bucket Capacity Standard	1.1 m ³
Backhoe Bucket Capacity	0.22 m ³
Operating Weight	9,480 kg

BELAZ-TURBO.RU

777A

BACKHOE LOADER

LIUGONG



TOUGH WORLD. TOUGH EQUIPMENT.

777A SPECIFICATIONS >>>

BELAZ-TURBO.RU

ENGINE

Emission Regulation	Tier 3 / Stage IIIA
Make	Perkins
Model	1104 - 44T
Gross Power	74.5 Kw (101 hp) @ 2,200 rpm
Net Power	72 Kw (98 hp) @ 2,200 rpm
Peak Torque	392 N · m @ 1,400 rpm
Displacement	4.4 L

ELECTRICAL SYSTEM

System Voltage	12 V
Battery Rating	95 amp - hr

DRIVE TRAIN

Number of Drive Wheels	4 wd
1st Maximum Speed, fwd/rev	6.6 km/h
2nd Maximum Speed, fwd/rev	10.8 km/h
3rd Maximum Speed, fwd/rev	24 km/h
4th Maximum Speed, fwd/rev	41 km/h
Turning Radius Outside of Front Tire	4,075 mm
Turning Radius Outside of Bucket	4,850 mm

BRAKES

Service Brake Type	wet disc
Service Brake Actuation	hydraulic service

TIRES

Front Tire Size	16.9-28 12RP TL
Rear Tire Size	16.9-28 12RP TL

HYDRAULIC SYSTEM


Circuit Type	open
Total Flow	143 L/min
Main Relief Pressure	24 MPa
Pump Type	tandem gear pump
Steering Type	priority valve

OPERATING WEIGHTS

Operating Weight	9,480 kg
------------------	----------

LOADER PERFORMANCE

Standard Bucket Type (referenced)	general load bucket 1.1 m ³
Standard Bucket Heaped Capacity ISO (referenced)	1.1 m ³



Standard Bucket Width (referenced)	2,260 mm
Lift Capacity at Full Height	33.2 kN
Bucket Breakout Force	59.6 kN
Maximum Dump Angle at Full Height	45°
Dump Height at Maximum Angle	2,691 mm
Dump Reach at Full Height Discharge	713 mm
Boom Lift Capacity, end, at ground	47.3 kN
Maximum Dig Depth	89 mm

BACKHOE PERFORMANCE


Standard Bucket Type (referenced)	general bucket 0.22 m ³
Standard Bucket Heaped Capacity ISO (referenced)	0.22 m ³
Standard Bucket Width (referenced)	762 mm
Maximum Dig Depth	4,390 mm
Reach From Swing Pivot at Ground	5,443mm
Turning Angle of Bucket	182°
Bucket Digging Force	58.2 kN
Dipper Digging Force, standard stick	37.5 kN
Loading Height	3,730 mm
Loading Reach from Swing Pivot	3,007 mm

SERVICE CAPACITIES

Fuel Tank	130 L
Engine Oil	8 L
Cooling System	16L
Hydraulic Reservoir	130 L
Hydraulic System Total	170 L
Transmission and Torque Converter	17 L
Axle, front	8.5 L
Axle, rear	13 L

STANDARD EQUIPMENT

Perkins1104D-44T
Carraro Transmission
Enclosed Cab, ROPS / FOPS with AC
Auxiliary Hydraulic Kit
Carraro4 x 4 Axles
Boom Interlock
General load Bucket 1.1 m ³
Seat belt



Guangxi Liugong Machinery Co., Ltd.

No. 1 Liutai Road, Liuzhou, Guangxi 545007, PR China
T: +86 772 3886124 E: overseas@liugong.com
www.liugong.com

05/2014 Designed by Liugong

Specifications and designs are subject to change without notice. Machines shown may include optional equipment.